



Declaration of Performance

nr. 034CPR01072013

Rev. 00

Decree 305/2011

Page 1 di 1

| | | |
|---|------------------------|---|
| 1 Product Unique Identification code: VBCM | | |
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: BOND CEMENT C2 T E Date and production place and/or other identification data are printed on packaging or BoL | | |
| 3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: CONCRETE BASED, TWO COMPONENTS FAST WATERPROOFER FORMULATED FOR THE APPLICATION AND THE SUPERPOSITION OF CERAMIC FLOORS OR COATING FOR BOTH INTERIOR AND EXTERIOR. (CM 01 P) | | |
| 4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5: <p style="text-align: center;">Winkler S.r.l. Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy Tel. +39 02/267.00.605 – Fax +39 02/267.00.621 info@winklerchimica.com www.winklerchimica.com</p> | | |
| 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2): <p style="text-align: center;">Not relevant (see 4)</p> | | |
| 6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V <p style="text-align: center;">System 3 for water impermeability System 4</p> | | |
| 7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: <p style="text-align: center;">Institute of Research and Tests M. MASINI S.r.L. Notified CE 0068 Laboratory Notified nr 0407</p> | | |
| 8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued : <p style="text-align: center;">TEST CERTIFICATE nr. 1592-2007 Test Report 323162/9012/CPR</p> | | |
| 9 Prestazione dichiarata: | | |
| Essential Characteristics | Performances | Harmonised Technical Specification |
| Initial Adhesion | 1,08 N/mm ² | UNI EN 14891:2012 |
| Adhesion after thermal cycles | 1,14 N/mm ² | |
| Adhesion after water immersion | 1,03 N/mm ² | |
| Adhesion strength after frosting-defrosting cycles | 1,28 N/mm ² | |
| Adhesion after contact with lime water | 0,98 N/mm ² | |
| Impermeability to water | None | |
| Crack-bridging capability (+23°C) | 1,25 mm | |
| Crack-bridging capability (- 5°C) | 1,05 mm | |
| Dangerous Substances Emission | None | |
| 10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4. | | |

Signed for and on behalf of the Manufacturer

Management and Quality Supervisor
Luigi Milani

Cologno Monzese July 2013