

1 Product Unique Identification code: <b>VJES VJSG</b>		
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: <b>ROYAL SUPER</b> Date and production place and/or other identification data are printed on packaging or BoL		
3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: <b>(C2T) Cement-based tile adhesive for indoor/outdoor laying of tiles or coverings.</b>		
4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5: <b>Winkler S.r.l.</b> <b>Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy Tel. +39 02/267.00.605</b> <a href="mailto:info@winklerchimica.com">info@winklerchimica.com</a> <a href="http://www.winklerchimica.com">www.winklerchimica.com</a>		
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2): <b>Not relevant</b>		
6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V <b>System 3</b>		
7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: <b>Product – Type determined by the notified test laboratory Istituto Masini, based on tests on samples provided by the manufacturer, according to System 3, issuing TEST REPORT no. 490-2008</b>		
8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued : <b>Not relevant</b>		
9 <b>Declared Performance:</b>		
<b>Essential Characteristics</b>	<b>Performances</b>	<b>Harmonised Technical Specification</b>
Open time: tensile adhesive strength:		UNI EN 12004 Ceramic tile adhesives <b>(C2T)</b>
- After 20 minutes	≥ 0.5 N/mm <sup>2</sup>	
Tensile adhesive strength:		
- Initial	≥ 1.00 N/mm <sup>2</sup>	
- After thermal aging	≥ 1.00 N/mm <sup>2</sup>	
- After water immersion	≥ 1.00 N/mm <sup>2</sup>	
- After frost and thaw acycles	≥ 1.00 N/mm <sup>2</sup>	
Slip	< 0.50 mm	
Dangerous Substances Emission	See MSDS	
10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4.		

Signed for and on behalf of the Manufacturer	Management and Quality Supervisor Luca Rossi
Cologno Monzese, April 2021	