

1 Product Unique Identification code: PWBN		
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: WINGRIP BITUMINOSO Date and production place and/or other identification data are printed on packaging or BoL		
3.Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: BITUMEN WATERPROOFING BONDING AGENT FOR APPLICATION OF CERAMIC FLOORS ON TERRACES, BALCONIES, SHOWER TRAYS AND TILES IN BATHROOMS (DM 01P).		
4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5: Winkler S.r.l. Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy Tel. +39 02/267.00.605 info@winklerchimica.com www.winklerchimica.com		
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (2): Not relevant		
6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V System 3 for Water resistance System 4		
7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: Water impermeability determined by the notified test laboratory (n. 0407) Istituto Giordano, based on test on samples taken by the manufacturer, according to system 3, releasing the TEST REPORT n. 323166/9011/CPR		
8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued : Not relevant		
9 Declared Performance:		
Essential Characteristics	Performances	Harmonised Technical Specification
Initial tensile adhesion strength	≥ 0.5 N/mm ²	UNI EN 14891:2012 waterproofing, liquid applied products, to be used under tile adhesive, glued by adhesives. (DM 01 P)
Adhesion after water immersion	≥ 0.5 N/mm ²	
Adhesion after frost and thaw cycles	≥ 0.5 N/mm ²	
Adhesion after thermal cycles	≥ 0.5 N/mm ²	
Adhesion after Calcium Hydroxide	≥ 0.5 N/mm ²	
Water resistance	No permeability	
Crack-Bridging (+23°C)	1.96 mm	
Crack-Bridging (-5°C)	1.82 mm	
Dangerous substances emission	See MSDS	
10. The performance of the product identified at points 1 and 2 is in conformità with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4..		

Signed for and on behalf of the Manufacturer

Management and Quality
Supervisor Luca Rossi

Cologno Monzese, April 2021

