

| | | |
|---|-----------------------------------|---|
| 1 Product Unique Identification code: PVONF | | |
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: ONE FLOORING Date and production place and/or other identification data are printed on packaging or Delivery note. | | |
| 3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: liquid waterproofing product for vehicular floors. | | |
| 4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5: <div style="text-align: center;"> Winkler S.r.l. Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italia Tel. +39 02/267.00.605 – Fax +39 02/267.00.621 info@winklerchimica.com www.winklerchimica.com </div> | | |
| 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2): Not relevant | | |
| 6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V System 3 for Fire Reaction System 4 | | |
| 7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: Reaction to fire determined by the notified testing laboratory (n.0006 L) CSI, based on tests on samples taken by the manufacturer, according to system 3, issuing the TEST REPORT N. 0609 \ DC \ REA \ 22_6 | | |
| 8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued : Not relevant | | |
| 9 Declared performance | | |
| Essential Characteristics | Essential Characteristics | Essential Characteristics |
| Wear resistance to rotating loads | $\leq RWA10 (\leq 10\text{cm}^3)$ | UNI EN 13813 Synthetic resin (RWA10-IR4-B2,0-F _{fl}) |
| Impact resistance | $\geq IR4 (\geq 20 \text{N.m})$ | |
| Adhesion strength | B2.0 ($\geq 2.0 \text{N/mm}^2$) | |
| Fire reaction | C _{fl} - s1 | |
| Dangerous Substances Emission | See MSDS | |
| 10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4. | | |

| | |
|---|---|
| Signed for and on behalf of the Manufacturer Cologno Monzese, 2022 May | Management and Quality Supervisor Luca Rossi  |
|---|---|